

# Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

**U.S. Department of Labor**  
Occupational Safety and Health  
Administration  
(Non-Mandatory Form)  
Form Approved  
OMB No. 1218-0072



IDENTITY <i>(As Used on Label and List)</i> <b>AirCare</b>	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
---	---

## Section I

Manufacturer's Name <b>AmeriDerm Laboratories, Ltd.</b>	Emergency Telephone Number <b>973-279-5100</b>
Address <i>(Number, Street, City, State, and ZIP Code)</i> <b>13 Kentucky Avenue</b>	Telephone Number for Information <b>973-279-5100</b>
<b>Paterson, NJ 07503</b>	Date Prepared <b>September 1, 2004</b>

## Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% <i>(optional)</i>
<b>Ethanol CAS # 64-17-5</b>				<b>50.0%</b>
<b>N- Propyl Acetate CAS # 109-60-4</b>				<b>.0006%</b>
<b>Isopropanol CAS # 67-63-0</b>				<b>10.0%</b>

## Section III - Physical/Chemical Characteristics

Boiling Point	<b>160 F</b>	Specific Gravity (H <sub>2</sub> O = 1) <b>0.910 @ 20 C</b>	
Vapor Pressure (mm Hg)		Melting Point	
Vapor Density (AIR = 1)	<b>Near Water</b>	Evaporation Rate (Butyl Acetate = 1) <b>Faster than water</b>	
Solubility in Water <b>Completely Soluable</b>			

Appearance and Odor  
**Pale Blue color with pleasant scent.**

### Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used)	Flammable Limits	LEL	UEL
Extinguishing Media <b>Alcohol foam, Dry-Chemical or water spray.</b>			
Special Fire Fighting Procedures <b>Product contains alcohol, use water spray to cool containers.</b>			
Unusual Fire and Explosion Hazards <b>Keep away from open sparks and flames. Flammable liquid, vapors are heavier than air and may cause ignition/flashback.</b>			

(Reproduce locally)

OSHA 174, Sept. 1985

### Section V - Reactivity Data

Stability	Unstable		Conditions to Avoid
	Stable <b>X</b>		<b>Heat sparks flames</b>
Incompatibility ( <i>Materials to Avoid</i> )			
Hazardous Decomposition or Byproducts			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	<b>X</b>	

### Section VI - Health Hazard Data

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?
Health Hazards ( <i>Acute and Chronic</i> ) <b>EYES – May cause eye irritation. INGESTION – Call a physician or local Poison Control Center immediately. Induce vomiting as directed by Medical Personnel.</b>			

Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
Signs and Symptoms of Exposure			
Medical Conditions Generally Aggravated by Exposure			
Emergency and First Aid Procedures <b>Flush eyes with water immediately – Call Physician.</b>			

**Section VII - Precautions for Safe Handling and Use**

Steps to Be Taken in Case Material is Released or Spilled <b>Normal clean up.</b>
Waste Disposal Method <b>Drain into sewer with plenty of water, if local regulations permit.</b>
Precautions to Be taken in Handling and Storing <b>Flammable</b>
Other Precautions <b>Do not spray into eyes.</b>

**Section VIII - Control Measures**

Respiratory Protection ( <i>Specify Type</i> )		
Ventilation	Local Exhaust <b>Normal</b>	Special <b>N/A</b>
	Mechanical ( <i>General</i> ) <b>N/A</b>	Other <b>N/A</b>
Protective Gloves <b>N/A</b>	Eye Protection <b>N/A</b>	
Other Protective Clothing or Equipment		
Work/Hygienic Practices		

\* U.S.G.P.O.: 1986 - 491 - 529/45775

