

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072



IDENTITY <i>(As Used on Label and List)</i> Instaclean	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
--	---

Section I

Manufacturer's Name AmeriDerm Laboratories, Ltd.	Emergency Telephone Number 973-279-5100
Address <i>(Number, Street, City, State, and ZIP Code)</i> 13 Kentucky Avenue	Telephone Number for Information 973-279-5100
Paterson, NJ 07503	Date Prepared 02-01-05
	Signature of Preparer <i>(optional)</i>

Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% <i>(optional)</i>
Isopropyl Alcohol		CAS# 67-63-0		

Section III - Physical/Chemical Characteristics

Boiling Point	190 F	Specific Gravity (H ₂ O = 1)	> than 1
Vapor Pressure (mm Hg)	N/A	Melting Point	N/A
Vapor Density (AIR = 1)	N/A	Evaporation Rate (Butyl Acetate = 1)	>than 1
Solubility in Water Soluble	ph 6.5-7.5		
Appearance and Odor Light blue gel with pleasant scent.			

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used) 60F	Flammable Limits	LEL	UEL
Extinguishing Media Carbon Dioxide, Dry Chemical, Alcohol-type foam			
Special Fire Fighting Procedures Product contains alcohol – Use water spray or cool containers.			
Unusual Fire and Explosion Hazards Flammable liquid – Keep away from sparks or open flames. Vapors are heavier than air and may cause ignition/flashback.			

(Reproduce locally)

OSHA 174, Sept. 1985

Section V - Reactivity Data

Stability	Unstable		Conditions to Avoid
	Stable	x	
Incompatibility (<i>Materials to Avoid</i>)			
Hazardous Decomposition or Byproducts			
Hazardous Polymerization	May Occur		Conditions to Avoid None known
	Will Not Occur	x	

Section VI - Health Hazard Data

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?
Health Hazards (<i>Acute and Chronic</i>) Vapors can be irritating to eyes. Severe eye irritation may occur if splashed in eyes. Swallowing – Slightly toxic. May cause dizziness, faintness, drowsiness, decreased awareness and responsiveness, lack of coordination, nausea, vomiting, abdominal discomfort, vomiting and diarrhea.			
Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?

Emergency and First Aid Procedures If splashed in eyes – flush with water immediately and call physician. If
swallowed and patient is fully conscious give two glasses of water. Induce
vomiting. This should be done only by medical or experienced first-aid personnel.
Obtain medical attention.

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled If local regulations permit, may be drained into sewer with water.
Waste Disposal Method Dispose of according to local, state, and federal regulations. May be drained into
sewer with plenty of water.
Precautions to Be taken in Handling and Storing Keep away from sparks and open flames.
Other Precautions

Section VIII - Control Measures

Respiratory Protection (<i>Specify Type</i>) N/A		
Ventilation	Local Exhaust N/A	Special N/A
	Mechanical (<i>General</i>) N/A	Other N/A
Protective Gloves N/A	Eye Protection N/A	
Other Protective Clothing or Equipment N/A		
Work/Hygienic Practices Normal use		

* U.S.G.P.O.: 1986 - 491 - 529/45775

